
Dimension



Properties


1	Connection	Disconnection or Short Circuit Be not Abnormal
2	Dielectric	AC 120V/0.5Sec or AC 100V/1min
3	Insulaton Resistance	100MΩ or more (DC100V)
4	Momentary Disconnection	No momentary disconnection of more than 1 micro second
5	Mated Connector Impedance (Differential)	90±15Ω (Mated Connector) ※Rise time : 50ps(20~80%)

Part number List


Part number	Product Name	L(mm)
530V-110	UB3-HF-SA0-MBS-0100-00K	1,000±25
530V-130	UB3-HF-SA0-MBS-0300-00K	3,000±50
530V-150	UB3-HF-SA0-MBS-0500-00K	5,000±100

(Cautions)
This cable ASSY single article satisfies no items specified as the cable ASSY of USB3.0 (Super Speed USB) standard of USB-IF standard organization issue.
Please adopt after carrying out system evaluation of the camera for machine visions.

Connection



Packing



Item	Model name · Article name
7	Label
6	Screw E-955
5	Mold (black) VM48950
4	USB3.0 MICRO-B Connector
3	Mold (black) VM48940
2	USB3.0 Standard-A Connector
1	Cable (black) 20379-FG-ALSV-8-MVT(USB3.0)BR

No.	Date	Contents for change

HIRAKAWA HEWTECH CORP.

Product Name: UB3-HF-SA0-MBS-0□00-00K
Part number: -
UNIT: mm
SPECIFICATION
File No. M-8574
1/1